



INSTALLATION INSTRUCTIONS

PART NUMBER: E-0643

This filter fits: SEE CATALOG FOR CURRENT APPLICATIONS

* **FREE K&N® decal** To register your warranty, please see us online at knfilters.com/register. **FREE K&N® decal** *
Congratulations, you have purchased the finest air filter that money can buy. With proper care, this filter will last 1 million miles or more. This filter is a direct replacement for the stock air filter, and no modification will be required. However the following procedures **MUST** be followed to ensure the proper fit and seal of the K&N® air filter.

If you need any assistance please call 1-800-858-3333 to speak with a representative in our Customer Service Center before returning the product.

INSTALLATION:

1. Use the manufacturer's recommended procedures to remove the air box lid.
2. Remove the dirty air filter by pulling it off the flange. (Fig. 1)
3. Position the hose clamp on the K&N® filter as shown, with the hex nut facing forward on the right side of the flange (leave the clamp loose). (Fig. 2)
4. Push the K&N® filter over the flange and position the hose clamp in the shown location. Use a screw driver or nut driver to tighten the clamp. (Fig. 3)
5. Re-install the air box lid into the vehicle and complete the installation using the manufacturer's recommended procedures.

THESE INSTRUCTIONS MUST BE FOLLOWED EVERY TIME THE FILTER IS SERVICED, OTHERWISE THE FILTER MAY NOT SEAL, AND DAMAGE TO THE ENGINE COULD RESULT.



Fig. 1



Fig. 2



Fig. 3